

CORRENTE DI CORTO CIRCUITO CONDIZIONATA – GDA/MERLIN GERIN- SCHNEIDER

[kA eff. 1"] (400/440 V c.a.)

Modello Interruttore	GDA (In)										
	63 A	100 A	160 A	250 A	400 A	500 A	630 A	800 A	1000 A	1250 A	1600 A
NSX100 B	10	10	10	13	27	29	33	35	40	42	50
NSX100 F	10	10	10	13	27	29	33	35	40	42	50
NSX100 N	10	10	10	13	27	29	33	35	40	42	50
NSX100 H	10	10	10	13	27	29	33	35	40	42	50
NSX100 S	10	10	10	13	27	29	33	35	40	42	50
NSX100 L	10	10	10	13	27	29	33	35	40	42	50
NSX100 R	10	10	10	13	27	29	33	35	40	42	50
NSX160 B			10	13	27	29	33	35	40	42	50
NSX160 F			10	13	27	29	33	35	40	42	50
NSX160 N			10	13	27	29	33	35	40	42	50
NSX160 H			10	13	27	29	33	35	40	42	50
NSX160 S			10	13	27	29	33	35	40	42	50
NSX160 L			10	13	27	29	33	35	40	42	50
NSX160 R			10	13	27	29	33	35	40	42	50

NSX250 B				26	27	29	33	35	40	42	50
NSX250 F				36	36	36	36	36	40	42	50
NSX250 N				50	50	50	50	50	50	50	50
NSX250 H				70	70	70	70	70	70	70	70
NSX250 S				100	100	100	100	100	100	100	100
NSX250 L				100	100	100	100	100	100	100	100
NSX250 R				100	100	100	100	100	100	100	100
NSX400 F					36	36	36	36	40	42	50
NSX400 N					50	50	50	50	50	50	50
NSX400 H					70	70	70	70	70	70	70
NSX400 S					100	100	100	100	100	100	100
NSX400 L					150	150	150	150	150	150	150
NSX400 R					200	200	200	200	200	200	200
NSX630 F						36	36	36	40	42	50
NSX630 N						50	50	50	50	50	50
NSX630 H						70	70	70	70	70	70
NSX630 S						100	100	100	100	100	100
NSX630 L						150	150	150	150	150	150
NSX630 R						200	200	200	200	200	200
NSX630bN							36	36	40	42	50
NS630bH							36	36	40	42	50
NS630bL							110	110	110	110	110
NS630bLB							180	180	180	180	180
NS800N								36	40	42	50

NS800H								36	40	42	50
NS800L								130	130	130	130
NS800LB								200	200	200	200
NS1000N									40	42	50
NS1000H									40	42	50
NS1000L									130	130	130
NS1250N										45	50
NS1250H										45	50
NS1600N											50
NS1600H											55